

09/379,239

WHAT IS CLAIMED IS:

1. A controller for a variable air volume terminal, of a variable air volume air conditioning system, comprising:

5 temperature sensing circuitry for generating a temperature process value;

setpoint determining circuitry for establishing a temperature setpoint;

10 airflow signal circuitry for generating an airflow setpoint in response to said temperature process value and said temperature setpoint;

flow sensing circuitry for generating a flow process value in response to a predetermined set of flow sensing inputs; and

15 damper control circuitry for generating a damper motor operation signal to control the damper motor in response to said flow process value and said airflow setpoint, said damper control circuitry comprising a fuzzy logic control mechanism for implementing a set of  
20 fuzzy logic rule-based instructions in generating said damper motor operating signal.

2. The controller of Claim 1, wherein said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, said flow sensing circuitry, and said damper control circuitry are  
25 formed sufficiently small for placement on a single

09379239.082399

printed circuit board, said printed circuit board formed for placement on the damper motor when said damper motor is installed in the damper shaft.

5           3.    The controller of Claim 1, wherein said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, and said flow sensing circuitry operate under an open protocol that permits system-wide control and monitoring of said controller within said variable air volume air conditioning system.

10           4.    The controller of Claim 1, wherein said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, and said flow sensing circuitry are associated to permit pressure dependent operation of said controller.

15           5.    The controller of Claim 1, wherein said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, and said flow sensing circuitry are associated to permit pressure independent operation of said controller.

20           6.    The controller of Claim 1, wherein said controller further comprises circuitry for permitting a

fire mode of operation for said variable air volume terminal.

5 7. The controller of Claim 1, further comprising circuitry for permitting a warm-up mode of operation for said variable air volume terminal.

10 8. The controller of Claim 1, further comprising circuitry for permitting remote control of said controller for controlling operation of said variable air volume terminal.

15 9. The controller of Claim 1, wherein said damper control circuitry further comprises circuitry for automatically calibrating the damper stroke of the damper in the variable air volume terminal.

20 10. The controller of Claim 1, wherein said damper control circuitry further comprises circuitry for manually driving the damper of the variable air volume terminal.

25 11. The controller of Claim 1, wherein said damper control circuitry further comprises circuitry for automatically stopping movement of the damper at a control stop position for the damper.

12. The controller of Claim 1, further comprising  
Hall Effect circuitry for identifying and controlling  
operation of said temperature sensing circuitry, said  
setpoint determining circuitry, said airflow signal  
5 circuitry, said flow sensing circuitry, and said damper  
control circuitry upon placing a predetermined magnet  
device proximate said Hall Effect circuitry.

13. The controller of Claim 1, wherein said damper  
10 control circuitry further comprises circuitry for  
counting alternating current voltage frequencies to said  
controller and determining from said alternating current  
voltage cycles the position of the damper in response to  
operation of said damper motor.

14. The controller of Claim 1, further comprising a  
shield surrounding said flow sensing circuitry for  
limiting affects of temperature variations on operation  
15 of said flow sensing circuitry.

15. A method for controlling a variable air volume terminal, having a damper and a damper motor, comprising the steps of:

generating a temperature process value using temperature sensing circuitry;

establishing a temperature setpoint using setpoint determining circuitry;

generating an airflow setpoint in response to said temperature process value and said temperature setpoint using airflow signal circuitry;

generating a flow process value in response to a predetermined set of flow sensing inputs using flow sensing circuitry; and

generating a damper motor operation signal using damper control circuitry to control the damper motor in response to said flow process value and said airflow setpoint, said damper motor operation signal generating step further comprising the step of implementing a set of fuzzy logic rule-based instructions in generating said damper motor operating signal.

16. The method of Claim 5, further comprising the step of forming said temperature sensing circuitry, said set point determining circuitry, said air flow signal circuitry, said flow sensing circuitry, and said damper control circuitry sufficiently small for their placement on a single printed circuit board, said printed circuit

board formed sufficiently small for placement on the damper motor when said damper motor is installed in the damper shaft.

5           17. The method of Claim 15, further comprising the  
step of operating said temperature sensing circuitry,  
said set point determining circuitry, said air flow  
10 signal circuitry, and said flow sensing circuitry under  
an open protocol that permits system-wide control and  
monitoring of said controller within said variable air  
volume air conditioning system.

15           18. The method of Claim 15, further comprising the  
step of associating said temperature sensing circuitry,  
said set point determining circuitry, said air flow  
signal circuitry, and said flow sensing circuitry to  
permit pressure dependent operation of said controller.

20           19. The method of Claim 15, further comprising the  
step of associating said temperature sensing circuitry,  
said set point determining circuitry, said air flow  
signal circuitry, and said flow sensing circuitry to  
permit pressure independent operation of said controller.

25           20. The method of Claim 15, further comprising the  
step of permitting a fire mode of operation for said  
variable air volume terminal.

21. The method of Claim 15, further comprising the step of operating said variable air volume terminal in a warm-up mode of operation.

5 22. The method of Claim 15, further comprising circuitry for permitting remote control of said controller for controlling operation of said variable air volume terminal.

10 23. The method of Claim 15, further comprising the step of automatically calibrating the damper stroke of the damper in the variable air volume terminal.

15 24. The method of Claim 15, further comprising the step of manually driving the damper of the variable air volume terminal.

20 25. The method of Claim 15, further comprising the step of automatically stopping movement of the damper at a control stop for the damper.

25 26. The method of Claim 15, further comprising the step of identifying and controlling operation of said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, said flow sensing circuitry, and said damper control circuitry by





29. A variable air volume air conditioning system,  
comprising:

a controller for a variable air volume terminal;

a variable air volume terminal comprising a damper,

5 a damper motor associated to move said damper, and a  
terminal controller for controlling operation of said  
damper motor, said terminal controller comprising:

temperature sensing circuitry for generating a  
temperature process value;

10 setpoint determining circuitry for establishing  
a temperature setpoint;

airflow signal circuitry for generating an  
airflow setpoint in response to said temperature  
process value and said temperature setpoint;

15 flow sensing circuitry for generating a flow  
process value in response to a predetermined set of  
flow sensing inputs; and

damper control circuitry for generating a  
damper motor operation signal to control the damper  
20 motor in response to said flow process value and  
said airflow setpoint, said damper control circuitry  
comprising a fuzzy logic control mechanism for  
implementing a set of fuzzy logic rule-based  
instructions in generating said damper motor  
25 operating signal.

5 30. The system of Claim 29, wherein said  
temperature sensing circuitry, said setpoint determining  
circuitry, said airflow signal circuitry, said flow  
sensing circuitry, and said damper control circuitry are  
formed sufficiently small for placement on a single  
printed circuit board, said printed circuit board being  
formed for placement on the damper motor when said damper  
motor is installed in the damper shaft.

10 31. The system of Claim 29, wherein said  
temperature sensing circuitry, said setpoint determining  
circuitry, said airflow signal circuitry, and said flow  
sensing circuitry operate under an open protocol that  
permits system-wide control and monitoring of said  
15 controller within said variable air volume air  
conditioning system.

20 32. The system of Claim 29, wherein said  
temperature sensing circuitry, said setpoint determining  
circuitry, said airflow signal circuitry, and said flow  
sensing circuitry are associated to permit pressure  
dependent operation of said controller.

25 33. The system of Claim 29, wherein said  
temperature sensing circuitry, said set point determining  
circuitry, said air flow signal circuitry, and said flow

sensing circuitry, are associated to permit pressure independent operation of said controller.

34. The system of Claim 29, wherein said controller further comprises circuitry for permitting a fire mode of operation for said variable air volume terminal.

35. The system of Claim 29, further comprising circuitry for permitting a warm-up mode of operation for said variable air volume terminal.

36. The system of Claim 29, further comprising circuitry for permitting remote control of said controller for controlling operation of said variable air volume terminal.

37. The system of Claim 29, wherein said damper control circuitry further comprises circuitry for automatically calibrating the damper stroke of the damper in the variable air volume terminal.

38. The system of Claim 29, wherein said damper control circuitry further comprises circuitry for manually driving the damper of the variable air volume terminal.

39. The system of Claim 29, wherein said damper control circuitry further comprises circuitry for automatically stopping movement of the damper at a control stop position for the damper.

40. The system of Claim 29, further comprising Hall Effect circuitry for identifying and controlling operation of said temperature sensing circuitry, said setpoint determining circuitry, said airflow signal circuitry, said flow sensing circuitry, and said damper control circuitry upon placing a predetermined magnet device in proximity to said Hall Effect circuitry.

41. The system of Claim 29, wherein said damper control circuitry further comprises circuitry for counting alternating current voltage frequencies to said controller and determining from said alternating current voltage cycles the position of the damper in response to operation of said damper motor.

42. The system of Claim 29, further comprising a shield surrounding said flow sensing circuitry for limiting affects of temperature variations on operation of said flow sensing circuitry.

43. A controller for an environmental control system, comprising:

temperature circuitry for receiving a signal representing a temperature process value;

5 setpoint circuitry for receiving a signal representing a temperature setpoint;

demand signal generating circuitry for generating a demand signal in response to said temperature process value and said temperature setpoint;

10 flow sensing circuitry for generating a flow process value in response to a predetermined set of flow sensing inputs; and

flow medium control signal generating circuitry for generating a flow medium control signal to control an actuator in response to said flow process value and said demand signal, said flow medium control signal generating circuitry comprising a fuzzy logic control mechanism for implementing a set of fuzzy logic rule-based instructions in generating said flow medium control signal.

20 44. The controller of Claim 43 wherein the flow medium control signal generating circuitry is operable to generate a flow medium control signal to an actuator, such that the flow medium control signal represents an  
25 offset, and wherein said offset represents an incremental move of the actuator.

- 5      45. The controller of Claim 43 wherein the flow medium control signal generating circuitry is operable to generate a flow medium control signal to an actuator, such that the flow medium control signal represents instructions to the actuator to move the actuator from a first position to a second position.

09379239.02239  
662220"6226/EE60



ATTORNEY DOCKET:  
019557.0121

REISSUE PATENT APPLICATION

64

flow medium control signal represents instructions to the  
actuator to move the actuator from a first position to a  
second position.

09379239 662280 66252650